

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representation of
The original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : F16L 55/00, A61M 5/32	A1	(11) International Publication Number: WO 94/08173 (43) International Publication Date: 14 April 1994 (14.04.94)
--	----	---

(21) International Application Number: PCT/US93/09450
(22) International Filing Date: 1 October 1993 (01.10.93)
(30) Priority data:
07/956,854 2 October 1992 (02.10.92) US
(60) Parent Application or Grant
(63) Related by Continuation
US 07/956,854 (CIP)
Filed on 2 October 1992 (02.10.92)
(71) Applicant (for all designated States except US): PALL CORPORATION [US/US]; 2200 Northern Boulevard, East Hills, NY 11548 (US).


(72) Inventor; and
(75) Inventor/Applicant (for US only): MATKOVICH, Vlado, I. [US/US]; 11 Old Estate Road, Glen Cove, NY 11542 (US).
(74) Agents: BUNDREN, William, J. et al.; 700 Thirteenth Street, N.W., Suite 300, Washington, DC 20005 (US).
(81) Designated States: AT, AU, BB, BG, BR, BY, CA, CH, CZ, DE, DK, ES, FI, GB, HU, JP, KP, KR, KZ, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SK, UA, US, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With international search report.
With amended claims.

(54) Title: CONNECTOR ASSEMBLY

(57) Abstract

A connector assembly includes first and second fittings (100, 200) and first and second membrane assemblies (170, 270). Each fitting (100, 200) defines a respective aperture (141, 231). Each membrane assembly has a layer (172a, 272a) sealing the aperture and a removable contamination containment layer (182a, 282a) overlying a respective sealing layer. The first and second fittings (100, 200) may be resiliently coupled in biased opposition to urge positive contact between the first and second removable contamination containment layers (182a, 282a) and/or the first and second sealing layers (172a, 272a). In one application, a connector assembly according to the invention may define a fluid communication path for handling a fluid without allowing the level of contaminants in the fluid to increase. A connector assembly according to the invention may be used to handle a biological fluid while maintaining the fluid free of viable contaminating microorganisms or preserving its sterility, for example.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NE	Niger
BE	Belgium	GN	Guinea	NL	Netherlands
BF	Burkina Faso	GR	Greece	NO	Norway
BG	Bulgaria	HU	Hungary	NZ	New Zealand
BJ	Benin	IE	Ireland	PL	Poland
BR	Brazil	IT	Italy	PT	Portugal
BY	Belarus	JP	Japan	RO	Romania
CA	Canada	KP	Democratic People's Republic of Korea	RU	Russian Federation
CF	Central African Republic	KR	Republic of Korea	SD	Sudan
CG	Congo	KZ	Kazakhstan	SE	Sweden
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovak Republic
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TG	Togo
CZ	Czech Republic	MG	Madagascar	UA	Ukraine
DE	Germany	ML	Mali	US	United States of America
DK	Denmark	MN	Mongolia	UZ	Uzbekistan
ES	Spain			VN	Viet Nam
FI	Finland				

Connector Assembly

Field of the Invention

The present invention relates to a connector assembly. More particularly, the invention relates to a connector assembly which maintains the sterility of a fluid, for example, a biological fluid, which passes through the connector assembly.

Background of the Invention

Connector assemblies have been developed to handle fluids, e.g., biological fluids, while preserving their condition. More particularly, connectors have been developed to preserve the condition of a fluid, or maintain a fluid free of contaminants. Freedom from contaminants refers to a relative amount of contaminants and is variously defined according to a specific industry, fluid and/or intended use. For example, a biological fluid which is substantially free of contaminants is considered free of viable micro-organisms, and is typically referred to as "sterile". Connector assemblies for use with biological fluids, for example, have been fashioned to preserve sterility of the fluid.

Attempts have been made to develop connector assemblies which isolate a fluid from the ambient environment of the connector, and from contaminants entrained in the ambient. Such connectors typically define a fluid conduit which is isolated from the ambient. Some conventional connector assemblies include mating male and female connectors having opposing, exposed surfaces. One surface may comprise the surface of a membrane, for example, while the other surface may comprise the surface of a rubber septum forming a blind end of an elastic, collapsible tube. These surfaces may be wiped with an antiseptic,

then resiliently urged in contact when the connectors are coupled. Other conventional connector assemblies provide a removable protective cover on each opposing surface to be contacted. These covers must be removed
5 prior to actually coupling the connectors.

Many problems are associated with these conventional connector assemblies. For example, wiping the surfaces with an antiseptic or removing the covers of these conventional connector assemblies may
10 not sufficiently protect the fluid flowing through these assemblies. The surfaces are wiped and the covers are removed usually by hand. Although the attendant may use surgical gloves, a gloved finger may trail the antiseptic wipe along the protected surface,
15 depositing on the surface contaminants that were on the glove. To unfasten and remove a cover, the gloved hand must manipulate the removable cover in intimate proximity to the protected surface under the cover, again risking incidental contact and the transmission
20 of contaminants between the glove and the protected surface.

In addition, once the surfaces are wiped with an antiseptic or the protective covers are removed from the protected surfaces, the surfaces are exposed to
25 the contaminant-laden ambient environment. For example, as the connectors are brought together, dust, micro-organisms, and other airborne contaminants may contact the protected surfaces, even if the connectors are quickly mated. Thus, while these conventional
30 connector assemblies have been developed to form a sterile connection, none adequately protect the fluid flowing through the connector assembly.

Summary of the Invention

Accordingly, the present invention provides a
35 connector assembly comprising first and second

fittings. The first fitting has a first aperture and the second fitting has a second aperture. In accordance with one aspect of the invention, each fitting includes a sealing layer sealing the aperture and the first and second fittings are resiliently coupled in biased opposition to urge positive contact between the sealing layers. In accordance with the second aspect of the invention each fitting includes a removable contamination containment layer and the first and second fittings are resiliently coupled in biased opposition to urge positive contact between the first and second removable contamination containment layers.

The invention also provides a connector assembly comprising first and second fittings, each fitting defining an aperture and including a removable layer overlying the aperture. The first and second fittings are coupled to form a housing and the removable layers include tab portions which extend to the exterior of the housing.

The invention further provides a connector assembly comprising first and second fittings and a resilient mount. The first fitting defines a first aperture and the second fitting defines a second aperture. The resilient mount is positioned between the first and second fitting and communicates with the first and second apertures. Further, the resilient mount includes a hub and a neck joined to the hub.

In addition, the present invention provides a method for making a contaminant-free connection, the method comprising the steps of (1) meeting a first fitting having a first removable contamination containment portion and a second aperture sealing portion with a second fitting having a second removable contamination containment portion and a second aperture sealing portion and (2) removing the

first and second contamination containment portions.

The present invention also provides a method of transferring fluid, the method comprising the steps of (1) resiliently coupling first and second fittings in biased opposition thereby providing positive contact between first and second removable contamination containment layers; (2) removing the first and second contamination containment layers; and (3) establishing a fluid flow path through the first and second fittings.

The methods and assemblies according to the invention may provide a contaminant-free fluid flow path by providing a membrane assembly having a contaminant containment layer or surface which can be removed to expose an underlying contaminant-free membrane or layer. In a preferred embodiment of the invention, structural elements of the fittings urge the membrane assemblies together, whereby access by contaminants is significantly reduced or eliminated.

Embodiments of the present invention may be used preferably with a sterile fluid, such as a biological fluid. A sterile fluid is one which is substantially free of viable contaminating microorganisms. Connector assemblies according to the invention define a fluid communication path wherein the fluid is maintained free of viable contaminating microorganisms, or the sterility of the fluid is not adversely affected by the passage of the fluid through the assembly.

The novel features and characteristics of this invention are set forth with particularity in the appended claims. However, the invention may best be understood with reference to the drawings, described below, and the accompanying detailed description of preferred embodiments.

Brief Description of the Drawings

Figure 1 is an elevation view, in partial section, of disassembled components of a connector assembly in one embodiment according to the invention.

5 Figure 2 is plan view of a female connector in the embodiment of figure 1.

Figure 3 is plan view of a male connector in the embodiment of figure 1.

10 Figure 4 is an elevation in cross section of a resilient mount in the embodiment of figure 1.

Figure 5a is a schematic of one embodiment of a membrane assembly according to the invention.

Figure 5b is a schematic of another embodiment of a membrane assembly according to the invention.

15 Figure 6 is an elevation view in partial section of the components of figure 1 in partial assembly.

Figure 7 is an elevation view in partial section, of the components of figure 1 in final assembly.

20 Figure 8 is an elevation view in partial section of a male connector in another embodiment of a connector assembly according to the invention.

Figure 9 is an elevation view in partial section of the male connector of figure 8, in final assembly.

25 Figure 10 is an elevation view in section of another embodiment of a female connector in a connector assembly according to the invention.

Figure 11 is an elevation view in partial section of the components of an alternative embodiment of the invention in partial assembly.

30 Figure 12 is an elevation view in partial section of the components of an alternative embodiment of the invention in final assembly.

Figure 13 is a plan view of a portion of the male connector in the embodiment of figure 11.

Detailed Description of the Invention

A connector assembly according to the present invention includes mating connectors or fittings which can be coupled to connect different fluid conduit sections, defining a fluid flow path, e.g., a liquid flow path. The connector assembly isolates the fluid flow path from the ambient environment and from contaminants present in the ambient environment and is preferably sterile. Consequently, a connector assembly according to the present invention is suitable for use in an open system, a closed system, or a closed sterile system.

In a preferred embodiment illustrated in figures 1-3, the connector assembly comprises two connectors, preferably a female connector 100 and a male connector 200. Each connector may be attached to any suitable fluid conduit section, for example, an inlet or outlet of a housing such as a blood filter. In the illustrated embodiment, the fluid conduits comprise sections of tubing 10, 20. Each connector may comprise any structure suitable to conduct fluid communication, preferably liquid communication, e.g. a housing of any form capable of containing fluid. The exemplary female connector 100, typically of unitary construction, generally comprises a fitting 130 and a membrane assembly 170. The exemplary male connector 200, typically of unitary construction, generally comprises a stem 210, a fitting 230 and a membrane assembly 270.

In the disassembled view of figure 1, the connectors are disposed generally opposing each other. For directional orientation in the following discussion, each connector has a proximate end, nearest the opposing connector, and a distal end, furthest from the opposing connector. Also, since the exemplary connectors 100, 200 in figure 1 comprise

generally elongated bodies, the term axial denotes disposition along their axes.

The female and male connectors may comprise a detent mechanism adapted to interlock the female connector in predetermined relation with the male connector. Thus, the female fitting 130 may include a bracket 148. The bracket 148 may be variously configured. The bracket 148 may comprise a socket or cup having any suitable plan form, e.g. rectangular or circular. In the illustrated embodiment, the bracket 148 comprises a U-shaped bracket or clevis. The representative bracket 148 is defined by a flange 150 and side walls 156. The flange 150 may assume a radially extending annular plan form, for example, as best seen in figure 2.

The side walls 156 depend away from the flange 150 and toward the opposing male connector 200. One or more tongues 158 may depend from the walls 156. The tongues 158 can be formed integrally with the walls 156, for example, by continuing middle sections of the walls 156. The tongues 158 can thus register in grooves 248 formed in a flange 246 of the male connector 200, best seen in figure 6. Accordingly, tongues 158 can be adapted to couple the female and male connectors 100, 200 in a tongue-in-groove engagement, as seen in the elevation view of figure 6 (in partial assembly). Tapers 162 can be formed at the proximate ends of the tongues 158 to guide the insertion of the tongues 158 into the grooves 248. Catches 160 can be formed which pass through the grooves 248, abutting a distal surface of the flange 246 and antagonistically locking the female and male connectors 100, 200, as will be detailed below.

A socket 164, adapted to receive the male connector 200, is defined by the space enclosed by the flange 150 and side walls 156. The proximate surface

of the flange 150 (i.e. the flange surface closest the opposing male connector) provides a socket or flange seat 152. The seat 152 serves as an abutment to the male connector 200 when the latter is positively engaged with the female connector 100.

The female fitting 130 may define an internal chamber or aperture 141 which may have any suitable configuration. The illustrated chamber 141 may comprise a bore 142 relieved at its proximate end into a counterbore 144. The flange seat 152 surrounds the counterbore 144. The illustrative female fitting 130 may be connected integrally with the section of tubing 10. The internal chamber 141 may be connected in fluid communication with the tubing 10.

In an important aspect of the invention, the female connector is adapted to contain or provide fluid communication and preferably defines an isolated portion of the fluid path, e.g., containing or conducting isolated fluid communication. Accordingly, the chamber 141 is enclosed by a membrane assembly 170. The assembly of the female and male connectors 100, 200 may be surrounded by an atmosphere or ambient environment having contaminants. In one key function, the membrane assembly 170 isolates the chamber 141, and fluid therein, from the surrounding ambient environment and from contaminants present in the ambient environment. Regardless of when or how the connector 100 is sterilized, the seal provided by the membrane assembly 170 is preferably secure enough to maintain the sterility within the chamber 141 of female connector 100. In the illustrated embodiment, the female connector 100 is formed such that the fitting 130, the flange 150, and membrane assembly 170 comprise integral portions of the female connector 100.

The membrane assembly is preferably secured to

the seat 152 of the female connector 100. Alternatively, the membrane assembly may be positioned in any other suitable location, such as within the internal chamber 141 and sealed to the walls of the bore or the counterbore. The membrane assembly 170 can be secured to the seat 152 or the walls of the chamber 141 by a variety of means. Preferably, the membrane assembly 170 can be secured by ultrasonic welding. Alternatively, the membrane assembly 170 may be secured by a heat seal or bonded by an adhesive or a solvent, preferably along the periphery.

Figures 1, 6, and 7 show elevation views of the male connector 200 in different stages of assembly with the female connector 100. Figures 1, 6, and 7 comprise views in partial section, as the stem 210 is shown in plain (i.e. non-sectioned) elevation. The male connector 200 generally includes a stem 210 housed in a fitting 230. The male connector 200 may also include a resilient mount 249 having a membrane assembly 270 secured thereto.

The male connector 200 is preferably adapted to contain and conduct fluid communication and preferably defines an isolated portion of the fluid flow path, e.g., containing or conducting isolated fluid communication. Accordingly, the stem 210 is preferably housed within a sealed chamber or aperture 231 defined within the fitting 230. In the illustrative embodiment, the stem 210 is hollow, defining a lumen (not shown) therein. The proximate end of the stem 210 may have a head 220 formed thereon. The head 220 may comprise a piercing element since it may have a sharpened tip. The head 220 may have an aperture providing fluid access between the lumen and the exterior of the stem 210. The stem 210 may also be connected to a fluid conduit section, e.g., the tubing section 20. If the stem 210 and

tubing 20 are fabricated as separate components, the tubing 20 may be joined to the base 223 using solvent, bonding or ultrasonic welding for example. Alternatively, the stem 210 and tubing 20 (or other
5 fluid conduit structure) may be molded as an integral part. The stem 210 may also be formed with a ratchet structure, for example beveled annular ribs 216 formed on the external surface of the stem 210. These ribs 216 are shown in plain, non-sectioned elevation in the
10 partially cross sectioned figures 1, 6 and 7. The ribs 216 may circumfuse the external surface of the stem 210. The ribs 216 may be beveled such that they project from the surface of the stem 210, extending distally toward the base 223 of the stem 210 and
15 forming an acute angle with the external surface of the stem 210.

Although the male connector may be variously configured, the illustrated male connector 200 comprises an arrangement of telescoping elements
20 adapted to house at least a portion of the stem 210 within the internal chamber 231 in isolation from contaminants. Thus, by way of illustration, the fitting 230 may have a generally cylindrical sleeve 232 extending from the flange 246. The sleeve 232
25 defines a bore 234 forming a portion of the internal chamber 231. The stem 210 may register intimately with the sleeve 232. In the illustrated embodiment, a portion of head 220 of the stem 210 is housed within the sleeve 232.

30 The illustrative male fitting 230 may further be constructed with a second outside sleeve 238 concentrically disposed about the first sleeve 232. The concentric sleeves 232, 238 may be connected by any appropriate means. In the representative
35 embodiment, the fitting 230 is formed such that the sleeves 232, 238 and the flange 246 comprise integral

portions of the fitting 230. Preferably, the outside sleeve 238 isolates both the stem 210 and the interior bore 234 of the inside sleeve 232 from exposure to the ambient environment. Thus, the axial length of the inside sleeve 232 may be shorter than the axial length of the outside sleeve 238. The remainder of the body of the stem 210 may be housed within an interior bore 239 defined within the outside sleeve 238.

The stem 210 may include a telescoping seal assembly adapted to mate in telescoping engagement with one or both of the sleeves 232, 238 to isolate and preferably seal the internal chamber 231. Generally, the telescoping seal assembly may be adapted to engage either sleeve, internally or externally. In the exemplary embodiment, the seal assembly 225 may mate in telescoping engagement at least with the interior bore 239 defined in the outside sleeve 238. The telescoping assembly may include elastomeric or deformable elements which intimately engage the walls of the interior bore 239. As shown in the representative embodiment of figures 1, 6, and 7, the illustrative telescoping assembly 225 may include a plunger 226 and an O-ring 227 which fits within a groove in the plunger 226. Preferably the plunger 226 and/or the O-ring 227 tightly engage the inside wall of the outside sleeve 238. This engagement advantageously isolates the interiors of both the inside and outside sleeves 232, 238 from the ambient environment.

The telescoping seal assembly may also mate with the inside sleeve 232 to seal the internal chamber 231. For this purpose, the distal end of the sleeve 232 may be formed with a rim 233. The rim 233 may assume a tapered form as shown. The telescoping seal assembly 225 may additionally include a shoulder 224 formed on a base 223 of the stem 210. The shoulder

224 may have a tapered form adapted to mate with that of the rim 233, providing another seal for the chamber 231.

Although the illustrated embodiment comprises an arrangement of telescoping elements, the male connector may include other arrangements for advancing the stem. For example, a screw mechanism with a ratchet may be mounted between the outer sleeve and stem. The stem could then be advanced by rotating the screw mechanism.

As exemplified in the plan view of the male connector 200 in figure 3, the flange 246 may be generally annular, circumfusing and extending radially from the sleeve 232. The flange 246 may be formed with one or more grooves 248. As mentioned above, the engagement of one or more tongues 158 of the female connector 100 in the grooves 248 of the male connector 200 is part of one possible structure for coupling the connectors 100, 200. This coupling is shown in an initial stage of engagement in figure 6.

In an important aspect of the invention, the female and male connectors may form a resilient coupling mechanism for engaging these connectors in biased opposition. Though this resilient coupling mechanism may be fashioned in a variety of ways, in the exemplary embodiment, this coupling mechanism may include the resilient mount 249. A representative construction for the resilient mount 249 is detailed in the sectioned elevation view of figure 4. The mount 249 serves as a seat which has at least one of the membrane assemblies secured thereon and which is at least axially resilient (e.g. at least resilient along an axis of the sleeve 232). The resilient mount 249 may be disposed generally between the female and the male connectors 100, 200, providing antagonism between the coupled connectors. The resilient mount

249 could be connected to the female connector 100. However, in the illustrated embodiment the resilient mount 249 is connected to the male connector 200.

As best shown in Figure 4, the mount 249 may include a resilient neck 252 connecting a hub 250 to the flange 246. The exemplary hub 250 defines a sealable seat surrounding an opening into the chamber 231. Thus, the hub 250 may have a wall 256 defining a well 262. The wall 256 may have an annular plan form, for example, as best shown in figure 3. The well 262 communicates with the bore 234 in the sleeve 232. Together, the illustrative bore 234 and well 262 may form the internal chamber 231. The wall 256 may further have a rim 258. This rim 258 forms the sealable seat circumfusing the well 262 which accesses the chamber 231. The membrane assembly 270 is preferably secured to the rim 258, enclosing the internal chamber 231.

As detailed particularly in figure 4, the neck 252 may be formed with a joint having a recess or groove, shown generally at 260. The grooved joint 260 connects the neck 252 to the hub 250, on the distal side of the hub. When the connectors 100, 200 are engaged, the grooved joint 260 yields, and the neck 252 is compressed at least axially. Thus, the axial resilience of the mount 249 urges the connectors into biased opposition, maintaining the membrane assemblies 170, 270 in positive contact. As one alternative to the grooved joint 260, the hub may be formed with a thin flange joining the neck.

The resilient mount 249 may be formed as an integral part of the male fitting 230. Thus, the sleeve 232, flange 246, neck 252 and/or hub 250 may be molded integrally for example. In this embodiment, the male fitting 230, like the female fitting 130, is molded as a single part from any suitable polymeric

material, for example olefinic compositions such as polypropylene, polyethylene, butadiene; acrylics; polycarbonates; or elastomers.

5 In the illustrated embodiment, the male connector 200 is formed such that the fitting 230, the resilient mount 249, and membrane assembly 270 comprise integral portions of the male connector 200.

10 Preferably, the female and male connectors 100, 200 are interlocked in predetermined relation and are resiliently coupled in antagonistic biased opposition. The coupling structure on each connector may be proportioned relative to the other to produce an antagonistic coupling. As noted above, figure 6 shows the tongue-in-groove coupling of the representative
15 female and male fittings 130, 230 in partial assembly. The tongues 158 and catches 160 abut the distal surface of the flange 246, interlocking the connectors 100, 200 in predetermined relation to each other. The dimensions of the fittings 130, 230 are preferably
20 proportioned such that when the catches 160 embrace the distal surface of the flange 246, the resilient mount 249, including the hub 250 and neck 252, compresses axially, forces the membrane assemblies 170, 270 into positive contact, and provides biased
25 opposition between the membrane assemblies 170, 270. To protect the resilient mount 249, shoulders 154a-154d, seen particularly in figures 1 and 2, may be formed preferably on the flange 148 of the female connector 100. These shoulders may serve as stops
30 limiting the compression of the mount 249 by ensuring a minimum spacing between the connectors. Alternatively, the mount 249 may be constructed such that it can tolerate compression that is limited by contact between the flanges 148, 246 and the hub 250.
35 Prior to coupling the connectors 100, 200, the proximate, opposing surfaces of the membrane

assemblies 170, 270, are exposed to the ambient environment. Upon coupling, these opposing surfaces are forced into positive contact with each other due to the biased opposition imposed by the resilient
5 mount 249. In a principal feature of the invention, this positive contact is maintained as long as the connectors 100, 200 are coupled. Through this positive contact, the contacting surfaces of the membrane assemblies 170, 270 cover each other,
10 isolating them from the ambient.

The membrane assemblies of the connectors may be variously configured and may be identical or not. Figures 5a and 5b are schematics showing different embodiments for the membrane assemblies. In a
15 principal aspect of the invention, each membrane assembly includes at least two layers or surfaces. The first comprises a removable contamination containment surface. Initially, this surface comprises the proximate surface of each respective
20 membrane assembly, i.e., the surface nearest and facing the opposing connector. The second surface of each membrane assembly comprises a protected sealing surface. This surface is protected and preferably isolated from the ambient environment and from
25 contaminants present in the ambient environment. At least initially, prior to the stage of inserting the stem into the female connector, the sealing surface seals the chamber defined within each respective fitting. In figures 5a and 5b, in the membrane
30 assembly 170 of the female connector 100, the sealing surface and the contamination containment surface are denoted by 174 and 182, respectively. In the membrane assembly 270 of the male connector 200, the sealing surface and the contamination containment surface are
35 denoted 274 and 282, respectively.

The layers or surfaces of the membrane assemblies

may be variously configured. In the exemplary embodiment of figure 5a, the contamination containment surface comprises a surface of a cover layer which may be completely removed from the membrane assembly.

5 This exposes a separate underlying sealing layer, having the sealing surface as one of its surfaces. In the embodiment of figure 5b, the contamination containment surface comprises a portion of a surface of a cover layer which is folded in a serpentine

10 configuration. This cover layer may be unfolded, exposing a protected cover layer portion, or may be removed completely, exposing a separate sealing layer.

Figure 5a shows one preferred embodiment of the membrane assemblies 170a, 270a. Each membrane

15 assembly 170a, 270a, in the illustrative embodiment, comprises two separate layers. The membrane assembly 170a has a cover layer 178a serving as a removable protective sheath covering a separate sealing layer 172a. The sealing surface 174a comprises the surface

20 of the sealing layer 172a facing the female flange 148. The contamination containment surface 182a comprises the surface of the cover layer 178a facing the male connector 200.

More particularly, the sealing layer 172a may

25 enclose the chamber 141 defined within the female fitting 130, preferably sealing it. Thus, the sealing surface 174a may be secured to the seat 152, preferably permanently, using any of the techniques discussed above, e.g. ultrasonic welding. In this

30 embodiment the sealing layer 172a is laid flat over the opening to the chamber 141 and because the sealing layer 172a has no folds, it has only two surfaces, the sealing surface 174a and an intermediate surface 176a. Also preferably, the sealing layer 172a may comprise

35 a material which precludes the passage of bacteria therethrough. This material may be porous, preferably

having a pore rating of about $0.2\mu\text{m}$ or less. Alternatively, the sealing layer 172a may comprise a material which is impervious to both liquid and gas. Accordingly, in one key function the membrane assembly
5 170a isolates a portion of the fluid path from the ambient environment and from contaminants in the ambient environment since the sealing layer 172a seals the chamber 141.

In the illustrated embodiment, the cover layer
10 178a is disposed over the sealing layer 172a in a single fold configuration. The exemplary cover layer 178a has a pull tab 179a (shown also in figure 2), an intermediate surface 180a and the contamination containment surface 182a. When the cover layer 178a
15 is attached to the sealing layer 172a, the intermediate surface 176a of the sealing layer 172a and the intermediate surface 180a of the cover layer 178a are interfaced in intimate contact. The cover layer 178a is preferably removably attached to the
20 sealing layer 172a in any suitable manner. The sealing layer 172a and the cover layer 178a can be attached together by heat sealing the perimeter of the intermediate surfaces 176a, 180a, for example. Alternatively, the intermediate surface 180a, but not
25 the contamination containment surface 182a, of the cover layer 178a has a tackiness or an adhesive which releasably holds the cover layer 178a to the sealing layer 172a but which entirely remains with the cover layer 178a when the cover layer 178a is removed from
30 the sealing layer 172a. The contamination containment surface 182a of the cover layer 178a and the intermediate surface 176a of the sealing layer 172a thus remain free of adhesive, preventing ambient contaminants from being attracted to and held by
35 either surface. Further, because the intermediate surface 176a of the sealing layer 172a remains free of

adhesive, there is no risk that the adhesive will leach into fluid flowing through the connector assembly.

Prior to coupling the female and male connectors 5 100, 200, the contamination containment surface 182a is exposed to the ambient environment. Preferably, the cover layer 178a also comprises a material, such as glassine paper, which precludes the passage of bacteria therethrough. Accordingly, while the cover 10 layer 178a is attached to the sealing layer 172a, it isolates the sealing layer from the ambient environment. In another key function of the membrane assembly 170a, the cover layer 178a protects the sealing layer 172a, isolating it from contact with 15 other surfaces, or surface area portions, or the ambient environment. More particularly, the cover layer 178a may be advantageously folded as shown so that the intermediate surface 180a intimately interfaces with the sealing layer 172a and protects 20 the sealing layer 172a from even the exposed contamination containment surface 182a.

The membrane assembly 270a of the male connector 200 has a construction analogous to that of the membrane assembly 170a. The membrane assembly 270a 25 has a sealing layer 272a and a cover layer 278a. The sealing surface 274a comprises the surface of the sealing layer 272a facing the male flange 246. The contamination containment surface 282a comprises the surface of the cover layer 278a facing the female 30 connector 100.

The sealing layer 272a seals the well 262, and thus the chamber 231 defined within the male fitting 230. Accordingly, the sealing surface 274a is secured to the rim 258 of the axially resilient hub 250. The 35 sealing surface 274a may be secured, preferably permanently, using any of the techniques outlined

above, e.g. ultrasonic welding. The sealing layer 272a may be laid flat over the well 262. Because the sealing layer 272a has no folds in this embodiment, it has two surfaces, the sealing surface 274a and an intermediate surface 276a. The sealing layer 272a may be impervious to gas or liquid or may comprise a porous, hydrophobic material which precludes the passage of bacteria therethrough. The sealing layer 272a thus isolates the chamber 231 from the ambient and from contaminants entrained in the ambient.

As in the female connector, the cover layer 278a may similarly be removably attached to the sealing layer 272a. This cover layer 278a may also be disposed over the sealing layer 272a in a single fold configuration. The exemplary cover layer 278a has a pull tab 279a (shown also in figure 2), an intermediate surface 280a and the contamination containment surface 282a. When the cover layer 278a is attached to the sealing layer 272a, the intermediate surface 276a of the sealing layer 272a and the intermediate surface 280a of the cover layer 278a are interfaced in intimate contact. Accordingly, while the cover layer 278a is attached to the sealing layer 272a, it isolates the sealing layer from the ambient and from contact with other surfaces exposed to the ambient.

In each of the previous embodiments of the membrane assemblies 170, 270, the cover layer 178, 278 intimately contacts the sealing layer 172, 272. However, the membrane assembly may alternatively be configured with the sealing layer spaced from the cover layer. For example, the cover layer may be removably attached to the flange of the connector, enclosing the chamber, while the sealing layer is spaced from the cover layer and positioned within the chamber sealed to the walls of the bore.

The antagonistic coupling of the connectors created by the tongue-in-groove engagement and the axially resilient mount 249 urges the respective contamination containment surfaces 182a, 282a, into
5 biased opposition. This resilience ensures positive contact between the contamination containment surfaces 182a, 282a as long as the connectors 100, 200 are coupled.

Preferably, the fittings 130, 230, and thus the
10 surfaces within the fittings defining the chambers 141, 231, may be sterilized either before or upon assembly with each other. Each of the sealing surfaces 174a, 274a seals its respective chamber 141, 231, isolating the chamber from the ambient and
15 contaminants entrained therein.

According to a principle aspect of the invention, each of the contamination containment surfaces 182a, 282a can be removed while maintaining these surfaces in positive contact. Once the connectors 100, 200 are
20 coupled, they form a housing and the pull tabs 179a, 279a of the cover layers 178a, 278a preferably abut each other and extend in the same direction to the exterior of the housing. For example, in the embodiment illustrated in Figure 6, the pull tabs
25 179a, 279a extend out of the channel of the U-shaped bracket 148 (i.e., into or out of the plane of the drawing page), beyond the assembly of the two connectors 100, 200. The pull tabs 179a, 279a can be pulled by hand, pinching the tabs together with two
30 fingers. The tabs 179a, 279a are most preferably pulled simultaneously, while maintaining the contamination containment surfaces 182a, 282a in biased contact. When the tabs are pulled together, the biased opposition of the resilient coupling
35 maintains the positive contact between the contamination containment surfaces 182a, 282a. Each

contamination containment surface 182a, 282a may trap and isolate any contaminants on the other. Even as the cover layers 178a, 278a are removed, the resilient mount 249 urges the contamination containment surfaces 182a, 282a into positive contact with each other. Also, a bacteriostatic or bacteriocidal compound or layer could be disposed on either or both contamination containment surfaces 182a, 282a. As the cover layers 178a, 278a are removed, each contamination containment surface 182a, 282a is pulled away from the respective sealing layer 172a, 272a by virtue of the advantageous fold configuration. Thus, in another key feature the membrane assemblies 170a, 270a isolate both the fluid path and surfaces intersecting the fluid path, e.g., the intermediate surfaces 176a, 276a at the sealing layers 172a, 272a, from the ambient and surfaces exposed to the ambient, e.g., contamination containment surfaces 182a, 282a.

In addition to being axially resilient, the resilient mount 249 is preferably flexible enough to tilt laterally or rock as the cover layers 178a, 278a are removed. Thus, as the cover layers 178a, 278a are removed, the hub 250 instantly urges the protected intermediate surfaces 176a, 276a of the sealing layers 172a, 272a into positive contact, virtually preventing contamination of these surfaces.

Each contamination containment surface 182a, 282a isolates the other, trapping therebetween any contaminants incident on the surfaces from the exposure of these surfaces to the ambient. The membrane assemblies 170a, 270a isolate both internal chambers 141, 231, and the fluid path portion defined within the stem 210, from the ambient. Further, the membrane assemblies 170a, 270a isolate both internal chambers 141, 231, and the fluid path portion defined within the stem 210, from surfaces exposed to the

ambient, e.g., from the contamination containment surfaces 182a, 282a. When the two connectors 100, 200 are coupled and the cover layers 178a, 278a are removed, only surfaces which were previously isolated
5 define or intersect the fluid flow path.

In the embodiment of figure 5b, each membrane assembly 170b, 270b comprises at least one sheet arranged in a serpentine fold configuration. Each fold defines a portion of the sheet forming a new
10 layer. Thus, the membrane assembly 170b can comprise a single sheet having one portion forming the sealing layer 172b. Another portion of the sheet after the first fold in the serpentine configuration forms a first cover layer 178b. Yet another portion of the
15 sheet after the second fold in the serpentine configuration forms a second cover layer 181b.

More particularly, the sheet portion forming the sealing layer 172b has two surfaces, a sealing surface 174b and an intermediate surface 176b. Analogous to
20 the embodiment of figure 5a, the sealing surface 174b may be secured to the seat 152 of the female fitting 130, preferably permanently. Preferably, the sealing layer 172b comprises a material which precludes the passage of bacteria. Thus the membrane assembly 170b
25 isolates a portion of the fluid path from the ambient and contaminants present in the ambient since the sealing layer 172b seals the chamber 141.

The first cover layer 178b may be removably attached to the sealing layer 172b as previously
30 discussed with respect to the embodiment shown in Figure 5a. The first cover layer 178b has an intermediate surface 180b. When the membrane assembly 170b is folded, the intermediate surface 176b of the sealing layer 172b and the intermediate surface 180a
35 of the first cover layer 178b are interfaced in intimate contact.

The second cover layer 181b may be disposed over the first cover layer 178b. The second cover layer 181b has a pull tab 179b and a contamination containment surface 182b. The contamination containment surface 182b comprises the surface of the membrane assembly 170b most proximate to the opposing male connector 200. Prior to coupling the female and male connectors 100, 200, the contamination containment surface 182b is exposed to the ambient. Preferably, the membrane assembly 170b comprises a homogeneous membrane sheet. Thus, both cover layers 178b, 181b also preclude the passage of bacteria therethrough. Accordingly, while the cover layers 178b, 181b are protectively disposed over the sealing layer 172b, they isolate the sealing layer from the ambient contaminants and from surfaces exposed to the ambient.

In the embodiment of figure 5b, the membrane assembly 270b of the male connector 200 can be constructed in a fashion analogous to the membrane assembly 170b of the female connector 100. Reference numerals for components of the membrane assembly 270b are analogous to the numerals for the membrane assembly 170b, except that the 200 series is used.

In use, the hollow stem 210 forms an isolated portion of the fluid communication path. On the proximate side of the internal chamber 231 of the male connector 200, the membrane assembly 270 preferably seals the hollow stem 210 therein. On the distal side of the chamber 231, the telescoping seal assembly 225 preferably seals the stem 210 therein. As exemplified in figure 7, in final assembly the stem 210 is adapted to bridge the chambers 141, 231. Accordingly, the stem 210 is free to move axially within the bore 234, toward the proximate end of the male fitting 230.

To establish fluid communication between the

internal chambers 141, 231, the connectors 100, 200 are first positively interlocked. The connectors 100, 200 may be interlocked by the tongue-in-groove coupling described above, for example. The resilient
5 mount 249 is then compressed and urges the cover layers of the membrane assemblies 170, 270 into positive contact against each other. The cover layers 178, 278 can then be removed by pulling the tabs 179, 279. The biased opposition provided by the resilient
10 mount 249 simultaneously urges the protected sealing layers of the membrane assemblies 170, 270 into positive contact against each other.

The stem 210 then can be advanced within the male fitting 230, typically by hand or by use of a tool.
15 The stem 210 may advance within the sleeves 232, 238 until the rim 233 formed on the distal end of the inside sleeve 232 abuts the shoulder 224 formed on the stem 210. The mating tapered surfaces of the rim 233 and the shoulder 224 provide yet another seal
20 isolating from the ambient the internal chamber 231 as well as the stem portion or head 220 therein. This abutment also serves as a stop, ultimately limiting the axial travel of the stem 210. The advance of the stem 210 is sufficient to allow the stem 210 to pierce
25 at least the sealing layer 172, 272 of each membrane assembly 170, 270, respectively. The head 220, which comprises a piercing element, may thus have a pointed form for example, adapted for this penetration. By inserting the stem 210 into the female fitting 130,
30 fluid communication is established between the female and male connectors 100, 200. Thus, the tubes 10, 20 are joined in fluid communication, and a single fluid path is formed through the connector assembly.

Preferably, once the stem 210 is inserted into
35 the female fitting 130, an axial restraint resists retraction of the stem 210. Such a restraint

preferably prevents altogether the retraction of the stem 210. This restraint is implemented in the illustrated embodiment by a ratchet or locking structure. The inside sleeve 232, including the tapered form of the rim 233 cooperates with the angle of the beveled ribs 216 to allow axial advance of stem 210 toward the female connector 100 with sufficient resistance to prevent accidental or incidental movement of the stem 210. The distal end of the inside sleeve 232 may further be formed with a lip or catch 236 depending radially inward within the bore 234. Upon attempting retraction of the stem 210, the beveled ribs 216 may engage the catch 236. This engagement prevents axial retraction of the stem 210, locking the stem within the female fitting 130. The ratchet structure may additionally include engagement of the beveled ribs 216 by an internal shoulder 235 (shown in figure 4) formed in the bore 234 of the sleeve 232, for example.

The axial restraint may also be implemented or augmented by the frictional telescoping engagement of mating parts. This includes the telescoping engagement of the plunger 226 and/or O-ring 227 within the bore 239. Also, both the head 220 of the stem 210 and the bore 142 defined within the female fitting 130 may comprise mating tapered forms. Accordingly, the head 220 may be lodged in frictional telescoping engagement within the internal chamber 141 of the female connector 100, sealing the stem 210 within the female connector 100 and resisting disengagement.

In another representative embodiment shown in figures 8 and 9, components corresponding to the previous embodiment are denoted with the same reference numerals. The illustrated seal assembly 225 may further include a frangible flange 228, in addition to the plunger 226. The outside sleeve 238

may have a seat assembly 240 formed at the distal end thereof. The frangible flange 228 may be fixed to the seat assembly 240 by any appropriate means, e.g. by bonding or welding, and may thus seal the interior
5 bore 239 defined within the outside sleeve 238. The seat assembly 240 may include a rim 242 which abuts the frangible flange 228 when the latter is fixed to the seat assembly. Preferably, the frangible flange 228 comprises an element which may be severed or
10 broken. More particularly, the frangible flange 228 may comprise a thin wall for example. Further, the frangible flange 228 may have a cleavage or crease formed on either side of the flange. The position of this crease would coincide with the area where the rim
15 242 abuts the frangible flange 228. Also, the rim 242 may advantageously form a sharp edge.

The assembly of connectors 100, 200 of the embodiment of figures 8 and 9 may operate similarly to the earlier embodiment. After the connectors 100, 200
20 are coupled and the removable cover layers are removed from the membrane assemblies 170, 270, the stem 210 can be advanced. The stem 210 may be forcibly advanced by hand or tool such that the flange 228 is severed or broken against the rim 242. As the stem
25 210 is advanced, the plunger 226 moves along the wall of the bore 239. The plunger 226 may again be advantageously formed from a compressible material, for example an elastomeric material. Contact between the plunger 226 and the wall of the bore 239 provides
30 a secure seal from the ambient for both bores 239, 234 and the internal chamber 231. Also, part of the frangible flange 228 remaining with the plunger 226 preferably comprises a material which may yield, compressing radially or folding at its periphery, for
35 example. Thus, the remaining portion of the severed flange 228 may initially enter and advance within the

bore 239 while constantly maintaining sealed contact with the tapering wall defining the bore 239.

In summary, in this embodiment of the connector assembly, at least four mechanisms advantageously cooperate to isolate from the ambient the distal end of the internal chamber 231. Originally, prior to advancing the stem 210, the frangible flange 228 may be fixed to the seat assembly 240, sealing the bore 239. Once the stem 210 is advanced, the periphery of the remaining portion of the frangible flange 228 intimately contacts the wall defining the bore 239. Similarly, the plunger 226 also intimately contacts the tapering wall of the bore 239. Finally, the abutting tapered surfaces of the rim 233 of the inside sleeve 232 and shoulder 224 of the stem 210 mate to seal the bore 234.

In an alternate embodiment, illustrated in Figures 11-12, the connector assembly comprises a female connector 100 and a male connector 200 as described above for Figures 1-4. In this embodiment of the invention, male connector 200 includes a stem 310 preferably housed within a sealed chamber or aperture 231 defined within a fitting 230. Male connector 200 includes an inside sleeve 232, the distal end of which may be formed with at least one lip or catch 236, as noted above. In the illustrated embodiment, the sleeve 232 has three catches 236 equally spaced from one another.

The stem 310 may also be formed with a first ratchet structure 311 and a second ratchet structure 312. For example, each ratchet structure 311 and 312 may include beveled annular ribs formed on the external surface of the stem 310. These ribs are shown in plain, non-sectioned elevation in the partially cross sectioned figures 11 and 12. The ribs may circumfuse the external surface of the stem 310.

The ribs may be beveled such that they project from the surface of the stem 310, extending distally toward the base 223 of the stem 310 and forming an acute angle with the external surface of the stem 310.

- 5 Tapers can be formed at the proximate end of the catches to guide the contact of the catches with the first and second ratchet structures.

 In a preferred embodiment, stem 310 also includes a relatively smooth external surface 313 between first
10 ratchet structure 311 and second ratchet structure 312, i.e., a surface which minimizes resistance to the movement of the stem 310 into the female connector 100 until fully engaged.

 In use, the hollow stem 310 forms an isolated
15 portion of the fluid communication path, as described above. The inside sleeve 232, including the tapered form of the rim 233 cooperates with the angled surface of the beveled ribs to allow axial advance of stem 310 toward the female connector 100 with sufficient
20 resistance to prevent accidental or incidental movement of the stem 310. The stem 310 can be advanced within the male fitting (CONNECTOR) 200 by applying sufficient force to overcome the engagement of the catch 236 with the beveled rib(s) of first
25 ratchet structure 311. In a preferred embodiment of the invention, the force required to move the rib(s) of the first ratchet structure 311 past the catch 236 is greater than the force required to move the rib(s) of the second ratchet structure 312 past the catch
30 236. For example, the bevel on the rib(s) of the first ratchet structure may be greater than the bevel on the rib(s) of the second ratchet structure.

 Once the stem 310 is inserted into the female fitting 130, an axial restraint resists retraction of
35 the stem 310. Such a restraint preferably prevents altogether the retraction of the stem 310. This

restraint is implemented in the illustrated embodiment by the second ratchet structure 312 which engages with catch 236. Upon attempting retraction of the stem 310, the engagement of the beveled ribs with the catch 236 prevents axial retraction of the stem 310, locking the stem within the female fitting 130.

As with all illustrated embodiments herein, a number of variations in the illustrated constructions are envisioned. For example, another embodiment for the female connector 100 is illustrated in Figure 10, where analogous components have the same reference numerals. In this embodiment, the counter bore 144 is closed at a blind end by a pierceable septum 147 and the septum 147 may comprise an integral part of the flange 150. Thus, the chamber 141 defined within the tubing 10 is sealed by both the membrane assembly 170 and the septum 147. The septum 147 may provide additional security in sealing the chamber 141 from ambient contaminants and from surfaces previously exposed to the ambient. The septum 147 may also resist the pressure of the fluid in the tubing section better than the membrane assembly 170. When the female and male connectors 100, 200 are coupled, the stem 210 can be axially advanced through the sleeve 232 to pierce three elements: the membrane assembly 270 of the male connector 200 and the membrane assembly 170 and the septum 147 of the female connector. In one possible mechanism for axial restraint of the stem, a throat may be formed where the septum is pierced, whereby the stem registers in an intimate friction fit within the throat.

Other variations are also envisioned. For example, where the female connector and fluid conduit comprise separate components, they could be connected by a variety of other means, e.g. mating threaded fittings. Alternatively, the bracket may be attached

to a sleeve, either formed integrally with the bracket or otherwise connected thereto. This sleeve may be connected to a section of tubing through telescopic engagement, i.e. a coaxial friction fit wherein one member is inserted within the other, with friction between the two members retaining the coupling. In another variant construction for the female connector, the two bores and the tubing can be variously configured. In the exemplary embodiment of figures 1-3 these components are generally cylindrical. Alternatively, they may be formed with cross sections of various geometries, for example rectangular or elliptical.

A number of variations are envisioned in the construction of the male connector. The hub and/or sleeve may assume cross sections of any suitable form, for example rhomboid or trapezoidal. Also, the sleeve, flange and/or hub, for example, can be molded or machined as separate parts, each with mating threads. The sleeve can also be constructed as separate, hollow telescoping sections housing a helical spring, for example. This may serve as a substitute for the illustrated construction of the resilient mount. The telescoping sections of the sleeve can be dimensioned to allow easy axial reciprocation of one half within the other. The spring would provide the resilience necessary to couple the connectors in biased opposition, maintaining positive contact between membrane assemblies. If the spring is helical, it can be sized such that the stem can be loosely housed, allowing for axial displacement within the helix. In another alternative to the illustrated construction of the resilient mount, the male fitting can alternatively be formed or machined as an integral piece from a post of elastomeric material. This post would be bored to

make it a hollow sleeve, and may be constructed without a separate hub piece. Alternatively, a separate elastomeric hub can be mounted on a sleeve piece.

5 The axial resilience in the coupling can alternatively be provided by using a deformable or resilient material for one or both sealing layers of the membrane assemblies. The resilience and thickness in the sealing layer should provide the compliance and
10 clearance necessary to urge the contamination containment surfaces into positive contact. Hence, the sealing layers may be made thick relative to the cover layers. The removable cover layers may be made thin relative to the sealing layers to make removal
15 easy while assuring positive contact of interfacing intermediate surfaces.

 The illustrated structure for coupling the female and male connectors can also be modified. The exemplary tongue-in-groove coupling can be replaced
20 with any coupling, preferably an interlocking structure which locks or becomes non-separable after coupling. A rabbeted coupling, for example, can be implemented by forming one connector with a groove or recess cut out of an edge or face of its body. The
25 other connector can be formed with a boss or rib having a shape that mates with that recess. In another alternative coupling, the female and male connectors can comprise any suitable form of mating threaded fittings.

30 Several alternative constructions for the axial restraint of the stem are possible. An axial restraint can be implemented by several embodiments of a friction fit, for example. The counter bore within the female fitting may be proportioned to accommodate
35 any flaps formed when the membrane assemblies are pierced. As the stem passes, the flaps can be pressed

radially against the inside wall of the counter bore. A tight friction fit may be formed with the flaps of the pierced membrane caught between the stem and the wall of the counter bore. Withdrawal of the stem from the female fitting may be prevented in part by friction. Forward edges of the membrane flaps may also engage the annular beveled ribs, preventing withdrawal of the stem.

In another alternative for the axial restraint, the stem and the male fitting may be formed as telescoping parts, coaxially engaging in a friction fit. These components may have tapered or conic sections, for example. Additionally or alternatively, these components may be formed with a rabbeted structure, e.g., a rib or lug may be formed on one component to engage in a mating recess formed in the other.

In the illustrated assembly of female and male connectors it may be desirable to ensure that accidental or incidental insertion of the stem through the membrane assemblies is prevented. Accordingly, the connector assembly can additionally be equipped with a mechanism initially preventing insertion of the stem. In one embodiment, this mechanism may be implemented by forming the proximate end of the stem with a relatively dull nipple rather than a head with a sharp tip. Additionally, the sealing and cover layers within a given membrane assembly could comprise different materials, e.g., materials which strongly resist being pierced by the stem. The nipple may also have a form which can penetrate one of the sealing or cover layers, but not the other. In another embodiment, this mechanism may comprise a cam structure. The connector housing the stem, e.g. the male fitting 230 in the illustrated embodiments, may have a slot formed in the sleeve and the stem may be

formed with a lug which serves as a cam. The cam can prevent axial advance of the stem when it abuts the rim of the sleeve, but upon twisting the stem to align the cam with the slot in the sleeve the stem 210 is
5 freed from the locking action of the cam. The stem may then be inserted into the female connector, piercing the membrane assemblies.

Claims:

1. A connector assembly comprising:
 - a first fitting defining a first aperture, and including a first membrane assembly sealing the first aperture, the first membrane assembly having at least one first removable portion; and
 - a second fitting defining a second aperture, and including a second membrane assembly sealing the second aperture, the second membrane assembly having at least one second removable portion;the first and second fittings being resiliently coupled in biased opposition to urge positive contact between the first and second removable portions.
2. The connector assembly of claim 1 wherein the first fitting has at least one tongue portion adapted to engage the second fitting and the second fitting has a resilient element adapted to engage the first fitting.
3. The connector assembly of claim 1 wherein at least one of the first and second fittings further comprises a telescoping housing defining a chamber and having a piercing member mounted in said housing.
4. The connector assembly of claim 3 wherein the piercing member includes a locking portion.
5. A connector assembly of claim 1 wherein the first and second removable portions are arranged to be removed after the first fitting is coupled with the second fitting.
6. A connector assembly of claim 1 wherein the removable portion is a layer.

7. A connector assembly comprising:

a first fitting defining a first aperture, and including a first sealing layer sealing the first aperture; and

5 a second fitting defining a second aperture, and including a second sealing layer sealing the second aperture;

wherein the first and second fittings are resiliently coupled in biased opposition to urge
10 positive contact between the first and second sealing layers.

8. A connector assembly comprising:

a first fitting defining a first aperture, and including a first removable layer overlying the
15 first aperture; and

a second fitting defining a second aperture, and including a second removable layer overlying the second aperture;

wherein the first and second fittings are resiliently coupled in biased opposition to urge
20 positive contact between the first and second removable layers.

9. A connector assembly comprising:

a first fitting defining a first aperture, and including a first removable layer overlying the
25 first aperture; and

a second fitting defining a second aperture, and including a second removable layer overlying the second aperture;

30 wherein the first and second fittings are coupled to form a housing and the first and second removable layers include tab portions which extend to the exterior of the housing.

10. A connector assembly comprising:
a first fitting defining a first aperture;
a second fitting defining a second aperture; and
5 a resilient mount positioned between the first
and second fitting and communicating with the first
and second apertures, the resilient mount including a
hub and a neck joined to the hub.

11. A method for making a contaminant-free
connection comprising:
10 mating a first fitting having a first removable
contamination containment portion and a first aperture
sealing portion with a second fitting having a second
removable contamination containment portion and second
aperture sealing portion; and
15 removing the first and second contamination
containment portions.

12. The method of claim 11 further comprising
piercing the first and second aperture sealing
portions with a piercing member.

20 13. The method of claim 12 further comprising
locking the piercing member.

14. The method of claim 11 wherein removing the
first and second contamination containment portions
comprises removing an exposed tab portion of the
25 contamination containment layer.

15. A method of transferring fluid comprising:
resiliently coupling first and second fittings in
biased opposition thereby providing positive contact
between first and second removable contamination
30 containment layers;
removing the first and second contamination

containment layers; and

establishing a fluid flow path through the first and second fittings.

5 16. The connector assembly of any one of claims 1, 7, 8, 9, or 10 wherein at least one of the first and second fittings further comprises a telescoping housing defining a chamber and having a stem mounted in said housing, said stem including at least two separated ratchet structures.

10 17. The connector assembly of claim 16 wherein the stem includes a first ratchet structure and a second ratchet structure.

15 18. The method of claim 15 wherein establishing a fluid flow path includes engaging a catch in contact with a first ratchet structure with a separate second ratchet structure, said ratchet structures included in at least one of the first and second fittings.

20 19. The method of claim 15 wherein establishing a fluid flow path includes moving a catch from engagement with a first ratchet structure to engagement with a second ratchet structure.

20 20. The method of claim 13 wherein locking the piercing member includes engaging a catch with a second ratchet structure.

25 21. The method of claim 15 wherein establishing a fluid flow path includes engaging a catch in contact with a ratchet structure included in at least one of the first and second fittings.

AMENDED CLAIMS

[received by the International Bureau
on 28 February 1994 (28.02.94);
new claims 22-28 added;
other claims unchanged (4 pages)]

22. A connector assembly comprising:

a first fitting defining a first aperture
and including a first membrane assembly sealing the
first aperture, the first membrane assembly
5 including at least one first removable portion and a
first sealing portion;

a second fitting defining a second
aperture and including a second membrane assembly
sealing the second aperture, the second membrane
10 assembly having at least one second removable
portion and a second sealing portion;

an interlock mechanism including at least
one tongue extending between the first and second
fittings and adapted to engage a corresponding catch
15 to interlock the first and second fittings, the
first and second fittings being resiliently coupled
in biased opposition to urge positive contact
between the first and second removable portions of
the membrane assemblies; and

20 a piercing member mounted in the first
fitting and axially movable through the sealing
portions of the first and second membrane assemblies
into the aperture of the second fitting.

23. A connector assembly comprising:

25 a first fitting defining a first aperture
and including a first sealing layer sealing the
first aperture;

a second fitting coupled to the first
fitting, defining a second aperture, and including a
30 second sealing layer sealing the second aperture;

a piercing member mounted in the first
fitting and axially movable through the sealing
layers into the aperture of the second fitting; and

a ratchet mechanism mounted to the piercing member to lock the piercing member within the second aperture of the second fitting.

24. A connector assembly comprising:

5 a first fitting defining a first aperture and including a first sealing layer overlying the first aperture;

a second fitting coupled to the first fitting, defining a second aperture, and including a
10 second sealing layer overlying the second aperture;

a piercing member mounted in the first fitting and axially movable through the sealing layers into the aperture of the second fitting; and

a frangible element sealingly connected
15 between the first fitting and the piercing member.

25. A connector assembly comprising:

a first fitting defining a first aperture and including a first membrane assembly having a first sealing layer sealing the first aperture and a
20 first removable layer overlying the first sealing layer;

a second fitting defining a second aperture and including a second membrane assembly having a second sealing layer sealing the second
25 aperture and a second removable layer overlying the second sealing layer;

a plurality of tongues extending between the first and second fittings and adapted to engage corresponding catches to interlock the first and
30 second fittings to form a housing, the first and second removable layers of the membrane assemblies including tab portions which extend to the exterior of the housing;

a resilient coupling mechanism including a

hub secured to at least one of the first and second membrane assemblies and a neck joined to the hub, the resilient coupling mechanism being adapted to resiliently urge positive contact between the first and second removable layers;

5 a piercing member including a head connected to a stem, the piercing member being telescopically mounted in the first fitting wherein the head is axially movable through the sealing layers of the first and second membrane assemblies and into sealing engagement with the second fitting;

10 a ratchet mechanism mounted between the stem of the piercing member and the first fitting to lock the head of the piercing member into sealing engagement with the second fitting; and

15 a seal cooperatively arranged between the piercing member and the first fitting.

27. A connector assembly comprising:

20 a first fitting defining a first aperture;
a second fitting defining a second aperture; and

a resilient mount positioned between the first and second fittings at the first and second apertures, the resilient mount and the first fitting comprising an integral, single, molded part formed from a polymeric material.

28. A method for making a contaminant-free connection comprising:

30 mating a first fitting and a second fitting; and

establishing a fluid flowpath through the first and second fittings by advancing a piercing member from the first fitting through a sealing member into the second fitting against a first

r sistance, a second resistance substantially less than the first resistance, and a third resistance substantially greater than the second resistance.

1/7




FIG. 1

2/7




FIG. 2




FIG. 3






FIG. 4

3/7

FIG. 5a**FIG. 5b**

4/7




FIG. 6




FIG. 7

6/7




FIG. 9

FIG. 8







FIG. 10



INTERNATIONAL SEARCH REPORT

 International application No.
 PCT/US93/09450

A. CLASSIFICATION OF SUBJECT MATTER

IPC(5) : F16L 55/00; A61M 5/32

US CL : 285/3; 604/283,411,905

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 285/3; 604/283,411,905

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched


Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 4,418,945 (KELLOGG) 06 DECEMBER 1983 (See entire document)	1-15
X	US, A, 5,122,123 (VAILLANCOURT) 16 JUNE 1992 (See entire document)	1-8, 10 AND 16-21
A	US, A, 4,636,204 (CHRISTOPHERSON) 13 JANUARY 1987	1-21
A	US, A, 4,019,512 (TENCZAR) 26 APRIL 1977	1-21
A	US, A, 4,030,494 (TENCZAR) 21 JUNE 1977	1-21
A,P	US, A, 5,195,993 (GIANAKOS) 23 MARCH 1993	1-21
A,P	US, A, 5,224,936 (GALLAGHER) 06 JULY 1993	1-21

☐ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* Special categories of cited documents:	* T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
* A		document defining the general state of the art which is not considered to be part of particular relevance
* E	* X	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
* L		document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
* O	* Y	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
* P	* &	document published prior to the international filing date but later than the priority date claimed
		document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
16 December 1993	30 DEC. 1993
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231	Authorized officer ERIC NICHOLSON 
Facsimile No. NOT APPLICABLE	Telephone No. (703) 308-2168